

Foreword

ISO (the International Organization for Standardization) and IEC (the International Electrotechnical Commission) form the specialized system for worldwide standardization. National bodies that are members of ISO or IEC participate in the development of International Standards through technical committees established by the respective organization to deal with particular fields of technical activity. ISO and IEC technical committees collaborate in fields of mutual interest. Other international organizations, governmental and non-governmental, in liaison with ISO and IEC, also take part in the work. In the field of information technology, ISO and IEC have established a joint technical committee, ISO/IEC JTC 1.

International Standards are drafted in accordance with the rules given in the ISO/IEC Directives, Part 3.

ISO/IEC 19757-3 was prepared by Joint Technical Committee ISO/IEC JTC 1, Information Technology, Subcommittee SC 34, Document Description and Processing Languages.

ISO/IEC 19757 consists of the following parts, under the general title *Document Schema Definition Languages (DSDL)*:

- *Part 1: Overview*
- *Part 2: Grammar-based validation — RELAX NG*
- *Part 3: Rule-based validation — Schematron*
- *Part 4: Namespace-based validation dispatching language — NVDL*
- *Part 5: Datatypes*
- *Part 6: Path-based integrity constraints*
- *Part 7: Character repertoire description language — CRDL*
- *Part 8: Document schema renaming language — DSRL*
- *Part 9: Datatype- and namespace-aware DTDs*
- *Part 10: Validation management*

Introduction

This International Standard defines a set of Document Schema Definition Languages (DSDL) that can be used to specify one or more validation processes performed against Extensible Stylesheet Language (XML) or Standard Generalized Markup Language (SGML) documents. (XML is an application profile SGML ISO 8879:1986.)

A document model is an expression of the constraints to be placed on the structure and content of documents to be validated with the model. A number of technologies have been developed through various formal and informal consortia since the development of Document Type Definitions (DTDs) as part of ISO 8879, notably by the World Wide Web Consortium (W3C) and the Organization for the Advancement of Structured Information Standards (OASIS). A number of validation technologies are standardized in DSDL to complement those already available as standards or from industry.

To validate that a structured document conforms to specified constraints in structure and content relieves the potentially many applications acting on the document from having to duplicate the task of confirming that such requirements have been met. Historically, such tasks and expressions have been developed and utilized in isolation, without consideration of how the features and functionality available in other technologies might enhance validation objectives.

The main objective of this International Standard is to bring together different validation-related tasks and expressions to form a single extensible framework that allows technologies to work in series or in parallel to produce a single or a set of validation results. The extensibility of DSDL accommodates validation technologies not yet designed or specified.

In the past, different design and use criteria have led users to choose different validation technologies for different portions of their information. Bringing together information within a single XML document sometimes prevents existing document models from being used to validate sections of data. By providing an integrated suite of constraint description languages that can be applied to different subsets of a single XML document, this International Standard allows different validation technologies to be integrated under a well-defined validation policy.

The structure of this part of ISO/IEC 19757 is as follows.

- [Part 5](#) describes the syntax of an ISO Schematron schema.
- [Part 6](#) describes the semantics of a correct ISO Schematron schema; the semantics specify when a document is valid with respect to an ISO Schematron schema.
- [Part 7](#) describes conformance requirements for implementations of ISO Schematron validators.
- [Annex A](#) is a normative annex providing the Part 2 (RELAX NG) schema for ISO Schematron.
- [Annex B](#) is a normative annex providing the ISO Schematron schema for constraints in ISO Schematron that cannot be expressed by the schema of [Annex A](#).
- [Annex C](#) is a normative annex providing the default query language binding to [XSLT](#).
- [Annex D](#) is a non-normative annex providing a DTD and corresponding ISO Schematron schema for a simple XML language Schematron Validation Report Language.
- [Annex E](#) is a non-normative annex providing motivating design requirements for ISO Schematron.
- [Annex F](#) is a normative annex allowing certain Schematron elements to be used in external vocabularies.
- [Annex G](#) is a non-normative annex with a simple example of a multi-lingual schema.

This part of ISO/IEC 19757 is based on the [Schematron](#)^[1] assertion language. The `let` element is based on [XCSL](#)^[2]. Other features arise from the half-dozen early Open Source implementations of Schematron in diverse programming languages and from discussions in electronic forums by Schematron users and implementers.

Document Schema Definition Languages (DSDL) — Part 3: Rule-based validation — Schematron

1 Scope

This part of ISO/IEC 19757 specifies Schematron, a schema language for XML.

Considered as a document type, a Schematron schema contains natural-language assertions concerning a set of documents, marked up with various elements and attributes for testing these natural-language assertions, and for simplifying and grouping assertions.

Considered theoretically, a Schematron schema reduces to a non-chaining rule system whose terms are boolean functions invoking an external query language on the instance and other visible XML documents, with syntactic features to reduce specification size and to allow efficient implementation.

Considered analytically, Schematron has two characteristic high-level abstractions: the pattern and the phase. These allow the representation of non-regular, non-sequential constraints that Part 2 cannot specify, and various dynamic or contingent constraints.

This part of ISO/IEC 19757 establishes requirements for Schematron schemas and specifies when an XML document matches the patterns specified by a Schematron schema.

2 Normative References

The following normative documents contain provisions which, through reference in this text, constitute provisions of this part of ISO/IEC 19757. For dated references, subsequent amendments to, or revisions of, any of these publications do not apply. However, parties to agreements based on this part of ISO/IEC 19757 are encouraged to investigate the possibility of applying the most recent editions of the normative documents indicated below. For undated references, the latest edition of the normative document referred to applies. Members of ISO and IEC maintain registers of currently valid International Standards.

Each of the following documents has a unique identifier that is used to cite the document in the text. The unique identifier consists of the part of the reference up to the first comma.

W3C XML 1.0, *Extensible Markup Language (XML) 1.0 (Third Edition)*, W3C Recommendation, 04 February 2004

XPath, *XML Path Language (XPath) Version 1.0*, W3C Recommendation, 16 November 1999

XSLT, *XSL Transformations (XSLT) Version 1.0*, W3C Recommendation, 16 November 1999

3 Terms and Definitions

3.1 abstract pattern

a pattern in a rule that has been parameterized to enable reuse

3.2 abstract rule

a collection of assertions which can be included in other rules but which does not fire itself

3.3 active pattern

a pattern belonging to the active phase

3.4 active phase

one particular phase, whose patterns are used for validation

3.5 assertion

a natural-language assertion with corresponding assertion test and ancillary attributes: assertions are marked up with `assert` and `report` elements

3.6 assertion test

an assertion modelled or implemented by a boolean query; an assertion test "succeeds" or "fails"

3.7 correct schema

schema that satisfies all the requirements of this part of ISO/IEC 19757

3.8 diagnostic

named natural language statements providing information to end-users of validators concerning the expected and actual values together with repair hints

3.9 elaborated rule context expression

a single rule context expression which explicitly disallows items selected by lexically previous rule contexts in the same pattern

3.10 good schema

a correct schema with queries which terminate and do not add constraints to those of the natural-language assertions. Note: It may not be possible to compute that a schema is good.

3.11 implementation

an implementation of a Schematron validator

3.12 name

a token with no whitespace characters

3.13 natural-language assertion

a natural-language statement expressing some part of a pattern; a natural-language assertion is "met" or "unmet"

3.14 pattern

a named structure in instances specified in a schema by a lexically-ordered collection of rules

3.15 phase

a named, unordered collection of patterns; patterns may belong to more than one phase; two names, `#ALL` and `#DEFAULT`, are reserved with particular meanings

3.16 progressive validation

the validation of constraints in stages determined or grouped to some extent by the schema author rather than, for example, entirely determined by document order

3.17 query language binding

a named set, specified in a document called a Query Language Binding, of the languages and conventions used for assertion tests, rule-context expressions and so on, by a particular Schematron implementation. Schematron is defined as a framework, with a default query language binding, but other query language bindings are possible. 6.4 specifies the information to be required by a query language binding and Annex C defines the default query language binding for Schematron.

3.18 rule

unordered collection of assertions with a rule-context expression and ancillary attributes

3.19 rule context

a selection of elements; a rule is said to fire when an information item matches its query

3.20 rule-context expression

a query to specify subjects; a rule-context is said to match an information item when that information item has not been matched by any lexically-previous rule context expressions in the same pattern and the information item is one of the information items that the query would specify

3.21 schema

specification of a set of XML documents

3.22 subject

a particular information item which corresponds to the object of interest of the natural-language assertions and typically is matched by the context expression of a rule

3.23 valid with respect to a schema

member of the set of XML documents described by the schema: an instance document is valid if no assertion tests in fired rules of active patterns fail

3.24 variable

a constant value, evaluated within the parent schema, phase, pattern or rule and scoped within the parent schema, phase, pattern or rule

4 Notation

4.1 XPath

This part of ISO/IEC 19757 uses [XPath](#) to identify information items in Schematron schemas.

4.2 Predicate Logic

This part of ISO/IEC 19757 uses predicate logic to express the semantics of Schematron schema. The following symbols are defined for use in s6.3:

- ()
Grouping delimiters
- \forall
"for all". Prefix operator.

- ¬
"not". Prefix operator.
- ∈
"is member of", in set operative sense. Prefix operator.
- ,
"and" (sequence). Infix operator.
- :
"where". Such that. Infix operator.
- ⇔
"if and only if". Infix operator.

5 Syntax

5.1 Well-formedness

A Schematron schema shall be a well-formed XML document, according to the version of XML used.

5.2 Namespace

All elements shown in the grammar for Schematron are qualified with the namespace URI:

```
http://purl.oclc.org/dsdl/schematron
```

In subsequent clauses, the prefix `sch` is taken as bound to the Schematron namespace URI for exposition purposes. The prefix `sch` is not reserved or required by this part of ISO/IEC 19757.

Any element can also have foreign attributes in addition to the attributes shown in the grammar. A foreign attribute is an attribute with a name whose namespace URI is neither the empty string nor the Schematron namespace URI. Any non-empty element may have foreign child elements in addition to the child elements shown in the grammar. A foreign element is an element with a name whose namespace URI is not the Schematron namespace URI. There are no constraints on the relative position of foreign child elements with respect to other child elements.

5.3 Whitespace

Any element can also have as children strings that consist entirely of whitespace characters, where a whitespace character is one of U+0020, U+009, U+00D or U+00A. There are no constraints on the relative position of whitespace string children with respect to child elements.

NOTE 1: Leading and trailing whitespace should be stripped from attributes defined by this part. Whitespace should be collapsed in elements defined by this part that allow text. Whitespace may be stripped from elements defined by this part that do not allow text.

5.4 Core Elements

The grammar for Schematron elements is given in [Annex A](#).

5.4.1 active element

The required `pattern` attribute is a reference to a pattern that is active in the current phase.

5.4.2 `assert` element

An assertion made about the context nodes. The data content is a natural-language assertion. The required `test` attribute is an assertion test evaluated in the current context. If the test evaluates positive, the report succeeds. The optional `diagnostics` attribute is a reference to further diagnostic information.

The natural-language assertion shall be a positive statement of a constraint.

NOTE 2: The natural-language assertion may contain information about actual values in addition to expected values and may contain diagnostic information. Users should note, however, that the `diagnostic` element is provided for such information to encourage clear statement of the natural-language assertion.

The `icon`, `see` and `fpi` attributes allow rich interfaces and documentation. They are defined below.

The `flag` attribute allows more detailed outcomes. It is defined below.

The `role` and `subject` attributes allow explicit identification of some part of a pattern. They are defined below.

5.4.3 `extends` element

Abstract rules are named lists of assertions without a context expression. The required `rule` attribute references an abstract rule. The current rule uses all the assertions from the abstract rule it extends.

5.4.4 `include` element

The required `href` attribute references an external well-formed XML document whose document element is a Schematron element of a type which allowed by the grammar for Schematron at the current position in the schema. The external document is inserted in place of the `include` element.

5.4.5 `let` element

A declaration of a named variable. If the `let` element is the child of a `rule` element, the variable is calculated and scoped to the current rule and context. Otherwise, the variable is calculated with the context of the instance document root.

The required `name` attribute is the name of the variable. The required `value` attribute is an expression evaluated in the current context.

It is an error to reference a variable that has not been defined in the current schema, phase, pattern, or rule, if the query language binding allows this to be determined reliably. It is an error for a variable to be multiply defined in the current schema, phase, pattern and rule.

The variable is substituted into assertion tests and other expressions in the same rule before the test or expression is evaluated. The query language binding specifies which lexical conventions are used to detect references to variables.

An implementation may provide a facility to override the values of top-level variables specified by `let` elements under the `schema` element. For example, an implementation may allow top-level variables to be supplied on the command line. The values provided are strings or data objects, not expressions.

5.4.6 `name` element

Provides the names of nodes from the instance document to allow clearer assertions and diagnostics. The optional `path` attribute is an expression evaluated in the current context that returns a string that is the name of a node. In the latter case, the name of the node is used.

An implementation which does not report natural-language assertions is not required to make use of this element.

5.4.7 `ns` element

Specification of a namespace prefix and URI. The required `prefix` attribute is an XML name with no colon character. The required `uri` attribute is a namespace URI.

NOTE 3: Because the characters allowed as names may change in versions of XML subsequent to [W3C XML 1.0](#), the RELAX NG Compact schema for Schematron does not constrain the prefix to particular characters.

In an ISO Schematron schema, namespace prefixes in context expressions, assertion tests and other query expressions should use the namespace bindings provided by this element. Namespace prefixes should not use the namespace bindings in scope for element and attribute names.

5.4.8 param element

A name-value pair providing parameters for an abstract pattern. The required `name` attribute is an XML name with no colon. The required `value` attribute is a fragment of a query.

5.4.9 pattern element

A structure, simple or complex. A set of rules giving constraints that are in some way related. The `id` attribute provides a unique name for the pattern and is required for abstract patterns.

The `title` and `p` elements allow rich documentation.

The `icon`, `see` and `fpi` attributes allow rich interfaces and documentation.

When a `pattern` element has the attribute `abstract` with a value `true`, then the pattern defines an abstract pattern. An abstract pattern shall not have a `is-a` attribute and shall have an `id` attribute.

Abstract patterns allow a common definition mechanism for structures which use different names and paths, but which are at heart the same. For example, there are different table markup languages, but they all can be in large part represented as an abstract pattern where a table contains rows and rows contain entries, as defined in the following example using the default query language binding:

```
<sch:pattern abstract="true" id="table">
  <sch:rule context="$table">
    <sch:assert test="$row">
      The element <name/> is a table. Tables contain rows.
    </sch:assert>
  </sch:rule>

  <sch:rule context="$row">
    <sch:assert test="$entry">
      The element <name/> is a table row. Rows contain entries.
    </sch:assert>
  </sch:rule>
</sch:pattern>
```

When a `pattern` element has the attribute `is-a` with a value specifying the name of an abstract pattern, then the pattern is an instance of an abstract pattern. Such a pattern shall not contain any `rule` elements, but shall have `param` elements for all parameters used in the abstract pattern.

The following example uses the abstract pattern for tables given above to create three patterns for tables with different names or structures.

```
<sch:pattern is-a="table" id="HTML_Table">
  <sch:param name="table" value="table"/>
  <sch:param name="row" value="tr"/>
  <sch:param name="entry" value="td|th"/>
</sch:pattern>

<sch:pattern is-a="table" id="CALIS_Table">
  <sch:param name="table" value="table"/>
  <sch:param name="row" value="..//row"/>
</sch:pattern>
```

```

    <sch:param name="entry" value="cell"/>
  </sch:pattern>

  <sch:pattern is-a="table" id="calendar">
    <sch:param name="table" value="calendar/year"/>
    <sch:param name="row" value="week"/>
    <sch:param name="entry" value="day"/>
  </sch:pattern>

```

When creating an instance of an abstract pattern, the parameter values supplied by the `param` element replace the parameter references used in the abstract patterns. The examples above use the default query language binding in which the character `$` is used as the delimiter for parameter references.

Thus, given the abstract patterns defined earlier in this clause, the patterns defined above are equivalent to the following, with the `id` elements shown expanded:

```

<sch:pattern id="HTML_table">
  <sch:rule context="table">
    <sch:assert test="tr">
      The element table is a table. Tables containing rows.
    </sch:assert>
  </sch:rule>

  <sch:rule context="tr">
    <sch:assert test="td|th">
      The element tr is a table row. Rows contain entries.
    </sch:assert>
  </sch:rule>
</sch:pattern>

<sch:pattern id="CALS_table">
  <sch:rule context="table">
    <sch:assert test="//row">
      The element table is a table. Tables containing rows.
    </sch:assert>
  </sch:rule>

  <sch:rule context="//row">
    <sch:assert test="cell">
      The element row is a table row. Rows contain entries.
    </sch:assert>
  </sch:rule>
</sch:pattern>

<sch:pattern id="calendar">
  <sch:rule context="calendar/year">
    <sch:assert test="week">
      The element year is a table. Tables containing rows.
    </sch:assert>
  </sch:rule>

  <sch:rule context="week">
    <sch:assert test="day">
      The element week is a table row. Rows contain entries.
    </sch:assert>
  </sch:rule>
</sch:pattern>

```

5.4.10 phase element

A grouping of patterns, to name and declare variations in schemas, for example, to support progressive validation. The required `id` attribute is the name of the phase. The implementation determines which phase to use for validating documents, for example by user command.

Two names, `#ALL` and `#DEFAULT`, have special meanings. The name `#ALL` is reserved and available for use by implementations to denote that all patterns are active. The name `#DEFAULT` is reserved and available for use by implementations to denote that the name given in in the `defaultPhase` attribute on the `schema` element should be used. If no `defaultPhase` is specified, then all patterns are active.

NOTE 4: The names `#ALL` and `#DEFAULT` shall not be used in a Schematron schema. They are for use when invoking or configuring schema validation, for example as a command-line parameter.

The `icon`, `see` and `fpi` attributes allow rich interfaces and documentation.

5.4.11 report element

An assertion made about the context nodes. The data content is a natural-language assertion. The required `test` attribute is an assertion test evaluated in the current context. If the test evaluates positive, the report succeeds. The optional `diagnostics` attribute is a reference to further diagnostic information.

The natural-language assertion shall be a positive statement of a found pattern or a negative statement of a constraint.

NOTE 5: The natural-language assertion may contain information about actual values in addition to expected values and may contain diagnostic information. Users should note, however, that the `diagnostic` element is provided for such information to encourage clear statement of the natural-language assertion.

The `icon`, `see` and `fpi` attributes allow rich interfaces and documentation. They are defined below.

The `flag` attribute allows more detailed outcomes. It is defined below.

The `role` and `subject` attributes allow explicit identification of some part of a pattern. They are defined below.

5.4.12 rule element

A list of assertions tested within the context specified by the required `context` attribute. The `context` attribute specifies the rule context expression.

NOTE 6: It is not an error if a rule never fires in a document. In order to test that a document always has some context, a new pattern should be created from the context of the document, with an assertion requiring the element or attribute.

The `icon`, `see` and `fpi` attributes allow rich interfaces and documentation.

The `flag` attribute allows more detailed outcomes. It is defined below.

The `role` and `subject` attributes allow explicit identification of some part of a pattern as part of the validation outcome. They are defined below.

When the `rule` element has the attribute `abstract` with a value `true`, then the rule is an abstract rule. An abstract rule shall not have a `context` attribute. An abstract rule is a list of assertions that will be invoked by other rules belonging to the same pattern using the `extends` element. Abstract rules provide a mechanism for reducing schema size.

5.4.13 schema element

The top-level element of a Schematron schema.

The optional `schemaVersion` attribute gives the version of the schema. Its allowed values are not defined by this part of ISO/IEC 19757 and its use is implementation-dependent.

The optional `queryBinding` attribute provides the short name of the query language binding in use. If this attribute is specified, it is an error if it has a value that the current implementation does not support.

The `defaultPhase` attribute may be used to indicate the phase to use in the absence of explicit user-supplied information.

The `title` and `p` elements allow rich documentation.

The `icon`, `see` and `fpi` attributes allow rich interfaces and documentation.

5.4.14 value-of element

Finds or calculates values from the instance document to allow clearer assertions and diagnostics. The required `select` attribute is an expression evaluated in the current context that returns a string.

Variable references in the `select` attribute are resolved in the scope of the current schema, phase, pattern and rule.

An implementation which does not report natural-language assertions is not required to make use of this element.

5.5 Ancillary Elements and Attributes

5.5.1 diagnostic element

A natural-language message giving more specific details concerning a failed assertion, such as found versus expected values and repair hints.

NOTE 7: in multiple languages may be supported by using a different `diagnostic` element for each language, with the appropriate `xml:lang` language attribute, and referencing all the unique identifiers of the `diagnostic` elements in the `diagnostics` attribute of the assertion. Annex G gives a simple example of a multi-lingual schema.

An implementation is not required to make use of this element.

5.5.2 diagnostics element

Section containing individual diagnostic elements.

An implementation is not required to make use of this element.

5.5.3 dir element

A section of natural-language text with a direction specified by the `value` attribute. The value `ltr` indicates left-to-right text; the value `rtl` indicates right-to-left text.

An implementation is not required to make use of this element.

5.5.4 emph element

A portion of text that should be rendered with some emphasis.

An implementation is not required to make use of this element.

5.5.5 flag attribute

A boolean variable with initial value false. A flag is implicitly declared by an assertion or rule having a `flag` attribute with that name. The value of a flag becomes true when an assertion with that flag fails or a rule with that flag fires.

The purpose of flags is to convey state or severity information to a subsequent process.

An implementation is not required to make use of this attribute.

5.5.6 `fpi` attribute

A formal public identifier for the schema, phase or other element.

An implementation is not required to make use of this attribute.

5.5.7 `icon` attribute

The location of a graphics file containing some visible representation of the severity, significance or other grouping of the associated element.

An implementation is not required to make use of this attribute.

5.5.8 `p` element

A paragraph of natural language text containing maintainer and user information about the parent element. The schema can nominate paragraphs that should be rendered in a distinct way, keyed with the `class` attribute.

An implementation is not required to make use of this element.

5.5.9 `role` attribute

A name describing the function of the assertion or context node in the pattern. If the assertion has a `subject` attribute, then the role labels the arc between the context node and any nodes which match the path expression given by the `subject` attribute.

An implementation is not required to make use of this attribute.

5.5.10 `see` attribute

The URI of external information of interest to maintainers and users of the schema.

An implementation is not required to make use of this attribute.

5.5.11 `span` element

A portion of some paragraph that should be rendered in a distinct way, keyed with the `class` attribute.

An implementation is not required to make use of this element.

5.5.12 `subject` attribute

A path allowing more precise specification of nodes. The path expression is evaluated in the context of the context node of the current rule. If no `subject` attribute is specified, the current subject node may be used.

NOTE 8: The `subject` attribute is required because the rule context may have been selected for reasons of convenience or performance, in association with the particular assertion tests. In such cases, the rule context may not be useful to identify users, and the nodes located by the `subject` attribute may be more useful. Similarly, it may not be possible to determine from an assertion test which nodes the assertion test has tested. In such a case, the nodes located by the `subject` attribute may be more useful.

An implementation is not required to make use of this element.

5.5.13 `title` element

A summary of the purpose or role of the schema or pattern, for the purpose of documentation or a rich user interface.

An implementation is not required to make use of this element.

6 Semantics

6.1 Validation Function

A general Schematron validator is a function returning "valid", "invalid" or "error". The function notionally performs two steps: transforming the schema into a minimal syntax, then testing the instance against the minimal syntax.

NOTE 9: This part of ISO/IEC 19757 does not constrain other information provided by an implementation nor other uses of Schematron schemas. However, it is the intent of this part of ISO/IEC 19757 to support implementations to provide rich, specific diagnostics customised with values that assist in detecting and rectifying problems.

A Schematron validator is a function over the following:

- a query language binding
- a schema document
- an instance to be validated
- external XML documents addressed using information in the instance or schema
- a phase name, or #ALL if all patterns shall be active patterns, or #DEFAULT if the `defaultPhase` attribute on the schema element shall be used
- a list of name-value pairs, if the schema uses external variables.

6.2 Minimal Syntax

To simplify the specification of semantics later, the following transformation steps are first applied to a schema, resulting in a schema in the minimal syntax:

1. Resolve all inclusions by replacing the `include` element by the resource linked to.
2. Resolve all abstract patterns by replacing parameter references with actual parameter values in all enclosed attributes that contain queries.
3. Resolve all abstract rules in the schema by replacing the `extends` elements with the contents of the abstract rule identified.
4. Negate all `report` elements into `assert` elements.
5. Remove elements used for diagnostics and documentation.

The resulting minimal syntax is also a valid Schematron instance in the full syntax. The minimal syntax differs from the complex syntax by not containing the following XPaths:

- `//sch:include`
- `//sch:pattern[@abstract="true"]`
- `//sch:pattern[@is-a]`
- `//sch:rule[@abstract="true"]`
- `//sch:extends`
- `//sch:report`

A schema language binding may also provide the following:

- The data models of the various query languages, the conversion between data models, and the treatment of information items: which information items are stripped or ignored, which information items are errors, and which information items are used.
- The `name` query language, a function which returns a data value coercible into a string.
- The `value-of` query language, a function which returns a data value coercible into a string.
- The `let` value query language, a function which returns a data value.
- The variable delimiter convention, a lexical convention such as a delimiter by which the use of a variable in a query expression shall be recognised.
- The abstract pattern parameter convention, a lexical convention such as a delimiter by which the parameters of abstract patterns inside query expressions shall be recognised.

The query language binding may also specify the element types in other namespaces which provide query-language-specific ancillary information or pragmatic hints.

The query language binding shall specify any whitespace processing required on queries.

The query language binding shall specify any restrictions to the value of name tokens.

A Schematron implementation which does not support the query language binding, specified in a schema with the `queryBinding` attribute, shall fail with an error.

6.5 Order and side-effects

The order in which elements are validated is implementation-dependent, without altering the validity of the instance.

The order in which patterns are used is implementation-dependent, without altering the validity of the instance.

The order in which assertions are tested is implementation-dependent, without altering the validity of the instance.

The only elements for which order is significant are the `rule` and `let` elements.

A `rule` element acts as an if-then-else statement within each pattern. An implementation may make order non-significant by converting rules context expressions to elaborated rule context expressions.

NOTE 12: The behaviour of the `rule` element allows constraints that would require a complex context expression to be factored into simpler expressions in different rules.

An `let` element may use lexically previous variables within the same rule or global variables.

NOTE 13: A wide variety of implementation strategies are therefore possible.

All queries shall act as pure functions. Queries shall not alter the instance in any way visible to other queries. This part of ISO/IEC 19757 does not specify any outcome augmentation of the instance being validated.

7 Conformance

7.1 Simple Conformance

A simple-conformance implementation shall be able to report for any XML document that its structure does not conform to that of a valid Schematron schema.

- A valid schema conforms to the constraints of [Annex A](#), the normative Part 2 (RELAX NG Compact Syntax) schema of this part of ISO/IEC 19757.

A simple-conformance implementation shall be able to determine for any XML document and for any good schema whether the document is valid with respect to the schema.

NOTE 14: It is not a requirement of this part of ISO/IEC 19757 that a simple-conformance implementation shall be able to determine whether validation will terminate or whether the queries are feasible against some other schema for the instance. The ability to determine these depends on the query language used. Where the query language allows incorrectness to be established, implementations are encouraged to report this information as part of validation.

NOTE 15: It is not a requirement of this part of ISO/IEC 19757 that a simple-conformance implementation shall be able to generate validation reports in the Schematron Validation Report Language, defined in [Annex D](#).

7.2 Full Conformance

A full-conformance implementation shall be able to determine for any XML document whether it is a correct schema.

- A valid schema conforms to the constraints of [Annex A](#), the normative Part 2 (RELAX NG Compact Syntax) schema of this part of ISO/IEC 19757.
- A valid schema conforms to the constraints of [Annex B](#), the normative ISO Schematron schema of this part of ISO/IEC 19757.
- A correct schema's attributes conform to the grammars specified by the query language binding in use.
- A correct schema has one definition only in scope for any variable name in any context.
- The values of the attributes `flag`, `id`, `name` and `prefix` are well-formed names in the version of XML being used.

A full-conformance implementation shall be able to determine for any XML document and for any good schema whether the document is valid with respect to the schema.

NOTE 16: It is not a requirement of that a full-conformance implementation shall be able to determine whether the validation will terminate or whether the queries are feasible against some other schema for the instance. The ability to determine these depends on the query language used. Where the query language allows incorrectness to be established, implementations are encouraged to report this information as part of validation.

NOTE 17: It is not a requirement of this part of ISO/IEC 19757 that a full-conformance implementation shall be able to generate validation reports in the Schematron Validation Report Language, defined in [Annex D](#).

Annex A (Normative)

RELAX NG schema for Schematron

A correct Schematron schema shall be valid with respect to the following Part 2 schema (RELAX NG Compact Syntax).

```
#      (c) International Organization for Standardization 2005.
#      Permission to copy in any form is granted for use with conforming
#      SGML systems and applications as defined in ISO 8879,
#      provided this notice is included in all copies.
default namespace sch = "http://purl.oclc.org/dsdl/schematron"
namespace local = ""
start = schema
# Element declarations
schema = element schema {
  attribute id { xsd:ID }?,
  rich,
  attribute schemaVersion { non-empty-string }?,
  attribute defaultPhase { xsd:IDREF }?,
  attribute queryBinding { non-empty-string }?,
  (foreign
  & inclusion*
  & (title?,
  ns*,
  p*,
  let*,
  phase*,
  pattern+,
  p*,
  diagnostics?))
}
active = element active {
  attribute pattern { xsd:IDREF },
  (foreign & (text | dir | emph | span)*)
}
assert = element assert {
  attribute test { exprValue },
  attribute flag { flagValue }?,
  attribute id { xsd:ID }?,
  attribute diagnostics { xsd:IDREFS }?,
  rich,
  linkable,
  (foreign & (text | name | value-of | emph | dir | span)*)
}
diagnostic = element diagnostic {
  attribute id { xsd:ID },
  rich,
  (foreign & (text | value-of | emph | dir | span)*)
}
diagnostics = element diagnostics {
  foreign & inclusion* & diagnostic*
}
dir = element dir {
  attribute value { "ltr" | "rtl" }?,
  (foreign & text)
}
```

```

emph = element emph { text }
extends = element extends {
  attribute rule { xsd:IDREF },
  foreign-empty
}

let = element let {
  attribute name { nameValue },
  attribute value { string }
}

name = element name {
  attribute path { pathValue }?,
  foreign-empty
}

ns = element ns {
  attribute uri { uriValue },
  attribute prefix { nameValue },
  foreign-empty
}

p = element p {
  attribute id { xsd:ID }?,
  attribute class { classValue }?,
  attribute icon { uriValue }?,
  (foreign & (text | dir | emph | span)*)
}

param = element param {
  attribute name { nameValue },
  attribute value { non-empty-string }
}

pattern = element pattern {
  rich,
  (foreign & inclusion* &
    ( (attribute abstract { "true" }, attribute id { xsd:ID },
        title?, (p*, let*, rule*))
      | (attribute abstract { "false" }?, attribute id { xsd:ID }?,
        title?, (p*, let*, rule*))
      | (attribute abstract { "false" }?, attribute is-a { xsd:IDREF },
        attribute id { xsd:ID }?, title?, (p*, param*))
    )
  )
}

phase = element phase {
  attribute id { xsd:ID },
  rich,
  (foreign & inclusion* & (p*, let*, active*))
}

report = element report {
  attribute test { exprValue },
  attribute flag { flagValue }?,
  attribute id { xsd:ID }?,
  attribute diagnostics { xsd:IDREFS }?,
  rich,
  linkable,
  (foreign & (text | name | value-of | emph | dir | span)*)
}

rule = element rule {
  attribute flag { flagValue }?,
  rich,
  linkable,
  (foreign & inclusion*
    & ((attribute abstract { "true" },

```

```

        attribute id { xsd:ID }, let*, (assert | report | extends)+)
    | (attribute context { pathValue },
        attribute id { xsd:ID }?,
        attribute abstract { "false" }?,
        let*, (assert | report | extends)+)))
}
span = element span {
    attribute class { classValue },
    (foreign & text)
}
title = element title {
    (text | dir)*
}
value-of = element value-of {
    attribute select { pathValue },
    foreign-empty
}
# common declarations
inclusion = element include {
    attribute href { uriValue }
}
rich =
    attribute icon { uriValue }?,
    attribute see { uriValue }?,
    attribute fpi { fpiValue }?,
    attribute xml:lang { langValue }?,
    attribute xml:space { "preserve" | "default" }?
linkable =
    attribute role { roleValue }?,
    attribute subject { pathValue }?
foreign =
    foreign-attributes, foreign-element*
foreign-empty =
    foreign-attributes
foreign-attributes =
    attribute * - (local:* | xml:*) { text }*
foreign-element = element * - sch:* {
    (attribute * { text }
    | foreign-element
    | schema
    | text)*
}
# Data types
uriValue = xsd:anyURI
pathValue = string
exprValue = string
fpiValue = string
langValue = xsd:language
roleValue = string
flagValue = string
nameValue = string # In the default query language binding, xsd:NCNAME
classValue = string
non-empty-string = xsd:token { minLength = "1" }

```

Annex B (Normative)

Schematron Schema for Additional Constraints

A correct Schematron schema shall be valid with respect to the following Schematron schema.

```

<!--
  (c) International Organization for Standardization 2005.
  Permission to copy in any form is granted for use with conforming
  SGML systems and applications as defined in ISO 8879,
  provided this notice is included in all copies.
-->

<sch:schema xmlns:sch="http://purl.oclc.org/dsdl/schematron"
  xml:lang="en" >
  <sch:title>Schema for Additional Constraints in Schematron</sch:title>
  <sch:ns prefix="sch" uri="http://purl.oclc.org/dsdl/schematron" />

  <sch:p>This schema supplies some constraints in addition to those
  given in the ISO RELAX NG Schema for Schematron.
  </sch:p>

  <sch:pattern>
    <sch:rule context="sch:active">
      <sch:assert
        test="//sch:pattern[@id=current()/@pattern]">
        The pattern attribute of the active element shall match the
        id attribute of a pattern.
      </sch:assert>
    </sch:rule>

    <sch:rule context="sch:pattern[@is-a]">
      <sch:assert
        test="//sch:pattern[@abstract='true'][@id=current()/@is-a]">
        The is-a attribute of a pattern element shall match
        the id attribute of an abstract pattern.
      </sch:assert>
    </sch:rule>

    <sch:rule context="sch:extends">
      <sch:assert
        test="//sch:rule[@abstract='true'][@id=current()/@rule]">
        The rule attribute of an extends element shall match
        the id attribute of an abstract rule.
      </sch:assert>
    </sch:rule>

    <sch:rule context="sch:let">
      <sch:assert
        test = "not(//sch:pattern
          [@abstract='true']/sch:param[@name=current()/@name])">
        A variable name and an abstract pattern parameter should not
        use the same name.
      </sch:assert>
    </sch:rule>

  </sch:pattern>
</sch:schema>

```

Annex C (Normative)

Default Query Language Binding

A Schematron schema with no language binding or a `language` attribute with the value `xslt`, in any mix of upper and lower case letters, shall use the following binding:

- The query language used is the extended version of [XPath](#) specified in [XSLT](#). Consequently, the data model used is the data model of those specifications.
- The rule context is interpreted according to the Production 1 of [XSLT](#). The rule context may be elements, attributes, comments and processing instructions.
- The assertion test is interpreted according to Production 14 of [XPath](#), as returning a boolean value.
- The name query is interpreted according to Production 14 of [XPath](#), as returning a string value. Typically, the `select` attribute contains an expression returning an element node: the name query takes the local or prefixed name of the node, not its value.
- The value-of query is interpreted according to Production 14 of [XPath](#), as returning a string value.
- The let value is interpreted according to Production 14 of [XPath](#), as returning a string value.
- The notation for signifying the use of parameter of an abstract pattern is to prefix the name token with the `$` character. This is a character not found as a delimiter in URLs or XPaths. The `$` character not followed by the name of an in-scope parameter shall not be treated as a parameter name delimiter. Such a character may subsequently be used as a delimiter for a variable name or as a literal character.
- A Schematron let expression is treated as an [XSLT](#) variable. The [XSLT](#) `$` delimiter signifies the use of a variables in an context expression, assertion test, name query, value-of query or let expression. The `$` character not followed by the name of an in-scope variable shall be treated as a literal character.

The [XSLT](#) `key` element may be used, in the [XSLT](#) namespace, before the pattern elements.

The attributes `id`, `name` and `prefix` should follow the rules for non-colonized names for the version of XML used by the document.

Annex D (Informative)

Schematron Validation Report Language

D.1 Description

The Schematron Validation Report Language (SVRL) is a simple XML language which may be used for reporting the results of Schematron validation and for conformance suites.

The order of elements in an SVRL is implementation-dependent; different implementations may generate the same elements in a different order.

D.2 DTD

```
<!--
    (c) International Organization for Standardization 2005.
    Permission to copy in any form is granted for use with conforming
    SGML systems and applications as defined in ISO 8879,
    provided this notice is included in all copies.
-->
<!ELEMENT schematron-output
    (text*, ns*, (active-pattern,
        (fired-rule, (failed-assert|successful-report)*))+)>

<!-- only active patterns are reported -->
<!ELEMENT active-pattern EMPTY>
<!-- only references are reported, not the diagnostic -->
<!ELEMENT diagnostic-reference (#PCDATA) >
<!-- only failed assertions are reported -->
<!ELEMENT failed-assert ( diagnostic-reference*, text )>
<!-- only rules that are fired are reported, abstract/extend handling
    should have been done before -->
<!ELEMENT fired-rule EMPTY >
<!-- only namespaces from sch:ns need to be reported -->
<!ELEMENT ns EMPTY >
<!-- only successful asserts are reported -->
<!ELEMENT successful-report ( diagnostic-reference*, text ) >
<!ELEMENT text (#PCDATA) >
<!ATTLIST schematron-output
    title CDATA #IMPLIED
    phase NMTOKEN #IMPLIED
    schemaVersion CDATA #IMPLIED >
<!ATTLIST active-pattern
    id ID #IMPLIED
    name CDATA #IMPLIED
    role NMTOKEN #IMPLIED >
<!ATTLIST diagnostic-reference
    diagnostic NMTOKEN #REQUIRED >
<!ATTLIST failed-assert
    id ID #IMPLIED
    location CDATA #REQUIRED
    test CDATA #REQUIRED
    role NMTOKEN #IMPLIED
    flag NMTOKEN #IMPLIED >
<!ATTLIST fired-rule
    id ID #IMPLIED
    context CDATA #REQUIRED
```

```

    role NMTOKEN #IMPLIED
    flag NMTOKEN #IMPLIED >

<!ATTLIST ns
  prefix NMTOKEN #REQUIRED
  uri CDATA #REQUIRED >
<!ATTLIST successful-report
  id ID #IMPLIED
  location CDATA #REQUIRED
  test CDATA #REQUIRED
  role NMTOKEN #IMPLIED
  flag NMTOKEN #IMPLIED >

```

D.3 Schematron Schema

The corresponding Schematron schema is:

```

<!--
  (c) International Organization for Standardization 2005.
  Permission to copy in any form is granted for use with conforming
  SGML systems and applications as defined in ISO 8879,
  provided this notice is included in all copies.
-->

<sch:schema
  xmlns:sch="http://purl.oclc.org/dsdl/schematron"
  xml:lang="en" >

  <sch:title>Schema for Schematron Validation Report Language</sch:title>

  <sch:p>The Schematron Validation Report Language is a simple language
  for implementations to use to compare their conformance. It is
  basically a list of all the assertions that fail when validating
  a document, in any order, together with other information such
  as which rules fire.
</sch:p>
  <sch:p>This schema can be used to validate SVRL documents, and provides
  examples of the use of abstract rules and abstract patterns.</sch:p>

  <sch:pattern>
    <sch:title>Elements</sch:title>
    <!--Abstract Rules -->
    <sch:rule abstract="true" id="second-level">
      <sch:assert test="../schematron-output">
        The <sch:name/> element is a child of schematron-output.
      </sch:assert>
    </sch:rule>

    <sch:rule abstract="true" id="childless">
      <sch:assert test="count(*)=0">
        The <sch:name/> element should not contain any elements.
      </sch:assert>
    </sch:rule>
    <sch:rule abstract="true" id="empty">
      <sch:extends rule="childless" />
      <sch:assert test="string-length(space-normalize(.)) = 0">
        The <sch:name/> element should be empty.
      </sch:assert>
    </sch:rule>

    <!-- Rules-->

```

```

<sch:rule context="schematron-output">
  <sch:assert test="not(../*)">
    The <sch:name/> element is the root element.
  </sch:assert>
  <sch:assert
    test="count(text) + count(ns) + count(active-pattern) +
      count(fired-rule) + count(failed-assert) +
      count(successful-report) = count(*)">
    <sch:name/> may only contain the following elements:
    text, ns, active-pattern, fired-rule, failed-assert
    and successful-report.
  </sch:assert>
  <sch:assert test="active-pattern">
    <sch:name/> should have at least one active pattern.
  </sch:assert>
</sch:rule>

<sch:rule context="text">
  <sch:extends rule="childless" />
</sch:rule>

<sch:rule context="diagnostic-reference">
  <sch:extends rule="childless" />
  <sch:assert test="string-length(@diagnostic) > 0">
    <sch:name/> should have a diagnostic attribute,
    giving the id of the diagnostic.
  </sch:assert>
</sch:rule>

<sch:rule context="ns">
  <sch:extends rule="second-level" />
  <sch:extends rule="empty" />
  <sch:assert
    test="following-sibling::active-pattern or following-sibling::ns">
    A <sch:name/> comes before an active-pattern or another
    ns element.
  </sch:assert>
</sch:rule>

<sch:rule context="active-pattern">
  <sch:extends rule="second-level" />
  <sch:extends rule="empty" />
</sch:rule>

<sch:rule context="fired-rule">
  <sch:extends rule="second-level" />
  <sch:extends rule="empty" />
  <sch:assert
    test="preceding-sibling::active-pattern |
      preceding-sibling::fired-rule |
      preceding-sibling::failed-assert |
      preceding-sibling::successful-report">
    A <sch:name/> comes after an active-pattern, an empty
    fired-rule, a failed-assert or a successful report.
  </sch:assert>
  <sch:assert test="string-length(@context) > 0">
    The <sch:name/> element should have a context attribute
    giving the current context, in simple XPath format.
  </sch:assert>
</sch:rule>

```

```

<sch:rule context="failed-assert | successful-report">
  <sch:extends rule="second-level" />
  <sch:assert
    test="count(diagnostic-reference) + count(text) = count(*)">
    The <sch:name/> element should only contain a text element
    and diagnostic reference elements.
  </sch:assert>
  <sch:assert test="count(text) = 1">
    The <sch:name/> element should only contain a text element.
  </sch:assert>
  <sch:assert test="preceding-sibling::fired-rule |
    preceding-sibling::failed-assert |
    preceding-sibling::successful-report">
    A <sch:name/> comes after a fired-rule, a failed-assert or a
    successful-report.
  </sch:assert>
</sch:rule>

<!-- Catch-all rule-->
<sch:rule context="*">
  <sch:report test="true">
    An unknown <sch:name/> element has been used.
  </sch:report>
</sch:rule>
</sch:pattern>

<sch:pattern>
  <sch:title>Unique Ids</sch:title>

  <sch:rule context="*[@id]">
    <sch:assert test="not(preceding::*[@id=current()/@id][1])">
      Id attributes should be unique in a document.
    </sch:assert>
  </sch:rule>
</sch:pattern>

<sch:pattern abstract="true" id="requiredAttribute">
  <sch:title>Required Attributes</sch:title>

  <sch:rule context=" $context ">
    <sch:assert test="string-length( $attribute ) > 0">
      The <sch:name/> element should have a
      <sch:value-of select="$attribute /name()" /> attribute.
    </sch:assert>
  </sch:rule>
</sch:pattern>

<sch:pattern is-a="requiredAttribute">
  <sch:param name="context" value="diagnostic-reference" />
  <sch:param name="attribute" value="@diagnostic" />
</sch:pattern>

<sch:pattern is-a="requiredAttribute">
  <sch:param name="context" value="failed-assert or successful-report" />
  <sch:param name="attribute" value="@location" />
</sch:pattern>

<sch:pattern is-a="requiredAttribute">
  <sch:param name="context" value="failed-assert or successful-report" />
  <sch:param name="attribute" value="@test" />
</sch:pattern>

```

```
<sch:pattern is-a="requiredAttribute">
  <sch:param name="context" value="ns" />
  <sch:param name="attribute" value="@uri" />
</sch:pattern>

<sch:pattern is-a="requiredAttribute">
  <sch:param name="context" value="ns" />
  <sch:param name="attribute" value="@prefix" />
</sch:pattern>

</sch:schema>
```

Annex E (Informative)

Design Requirements

Motivating design requirements for the schema language with the default query language binding include:

1. Represent abstract patterns such as the head+body pattern.
2. Support progressive validation.
3. Include assertions or abstract rules from an external file.
4. Support a one-to-one mapping between the natural-language statements and artificial-language statements.
5. Support the generation and labelling of arcs between information items.

Motivating design requirements for the schema language with the default query language binding do not include:

- Simple specification of constraints that are simply expressed by grammar-based validation, such as Part 2 (RELAX NG) schemas or DTDs.
- Replacement of any other standard schema language for XML.
- Single-pass or streamable implementation.

As well, certain outcomes are out-of-scope for this part of ISO/IEC 19757:

- Specification of a type system.
- Generation of links between multiple occurrences of some datum across multiple documents for the purpose of consistency-checking.

Annex F (Normative)

Use of Schematron as a Vocabulary

The following Schematron element types may be used as vocabulary elements by other standards and schemas. The semantics of element types used externally shall follow this part of ISO/IEC 19757.

- `schema`
- `pattern`
- `rule`
- `assert`
- `report`

These elements should use the standard Schematron namespace specified in [5.2](#).

When Schematron elements other than the `schema` element are used as vocabulary elements by other standards and schemas, the other standard or schema should specify mechanisms for defining information otherwise supplied by Schematron elements, such as `ns` or `let`.

Annex G (Informative)

Use of Schematron for Multi-Lingual Schemas

The following Schematron schema shows how multiple languages may be supported.

```
<sch:schema xmlns:sch="http://purl.oclc.org/dsdl/schematron"
  xml:lang="en" >
  <sch:title>Example of Multi-Lingual Schema</sch:title>
  <sch:pattern>
    <sch:rule context="dog">
      <sch:assert test="bone" diagnostics="d1 d2">
        A dog should have a bone.
      </sch:assert>
    </sch:rule>
  </sch:pattern>

  <sch:diagnostics>
    <sch:diagnostic id="d1" xml:lang="en">
      A dog should have a bone.
    </sch:diagnostic>
    <sch:diagnostic id="d2" xml:lang="de">
      Das Hund muss ein Bein haben.
    </sch:diagnostic>
  </sch:diagnostics>
</sch:schema>
```

Bibliography

- [1] Schematron, *Resource Description for Schematron (web page)*, Rick Jelliffe, Computing Centre, Academia Sinica, Taipei, <http://purl.oclc.org/dsdl/schematron>
- [2] XCSL, *XML Constraint Specification Language*, José Carlos Leite Ramalho, Department of Informatics, School of Engineering, University of Minho, <http://www.di.uminho.pt/~jcr/PROJS/xcsel-www/>